


Flexible Coupling



Nominal Size mm/in	Pipe OD mm/in	Bolt Size mm	Dimensions mm			Working Pressure Psi/Mpa	Certificate
			Φ	L	H		
25 1	33.7 1.327	2-M10×45	57	97	44	300 2.07	FM UL
32 1¼	42.4 1.669	2-M10×45	67	107.5	44	300 2.07	FM UL
40 1½	48.3 1.9	2-M10×45	72	114	44	300 2.07	FM UL
50 2	60.3 2.375	2-M10×55	85	125	45	300 2.07	FM UL
65 2½	73 2.875	2-M10×55	98	137	45	300 2.07	FM UL
65 2½	76.1 3	2-M10×55	100	139	45	300 2.07	FM UL
80 3	88.9 3.5	2-M10×55	114	160	45	300 2.07	FM UL
100 4	108.3 4.25	2-M12×65	140	186	50	300 2.07	FM UL
100 4	114.3 4.5	2-M12×66	147.2	193	50	300 2.07	FM UL
125 5	133 5.25	2-M12×75	164	216	50	300 2.07	FM UL
125 5	139.7 5.5	2-M12×75	170	222	50	300 2.07	FM UL
125 5	141.3 5.563	2-M12×75	170	222	50	300 2.07	FM UL
150 6	159 6.25	2-M12×75	194	246	50	300 2.07	FM UL
150 6	165.1 6.5	2-M16×85	203	248	50	300 2.07	FM UL
150 6	168.3 6.625	2-M16×85	205	254	50	300 2.07	FM UL
200 8	219.1 8.625	2-M20×120	257	330	58	300 2.07	FM UL
250 10	273 10.75	2-M22×140	328	420	62	300 2.07	FM UL
300 12	323.9 12.75	2-M22×140	380	454	63	300 2.07	FM UL